



LC/APC connector

Connector Type LC/APC 8°, according IEC 61754
 Color: Green
 Ferrule Zirconia Grade C
 Insertion loss avg = 0,25 dB
 97% $\leq$ 0,5 dB, random mated
 100 % $\leq$ 0,7 dB, random mated
 100 % $\leq$ 0,3 dB, against reference connector
 Return loss Typ. $\geq$ 65 dB, Min $\geq$ 65 dB
 Temperature range -25 °C t/m +70 °C

LC/APC connector

Connector Type LC/APC 8°, according IEC 61754
 Color: Green
 Ferrule Zirconia Grade C
 Insertion loss avg = 0,25 dB
 97% $\leq$ 0,5 dB, random mated
 100 % $\leq$ 0,7 dB, random mated
 100 % $\leq$ 0,3 dB, against reference connector
 Return loss Typ. $\geq$ 65 dB, Min $\geq$ 65 dB
 Temperature range -25 °C t/m +70 °C

Pigtailcord

Cord-diameter: 1,2 mm
 Type: Tight buffered
 Fiber: ITU-T G.657A1
 Sheath: Yellow LSZH.
 Length: 2,5 and 4,5 meter

Temperature range including connector -25 °C t/m +70 °C

LGCE
 Energieweg 19
 3281 NH Numansdorp
 the Netherlands
 Tel: +31 18 665 95 10
 E-mail: info@lgce.net



Date signed:	01/02/2018	
Drawn by:	AR/LGCE	
	Rev. 1.0a	
Art:	SM LC/APC-LC/APC 1.2MM	