

Meraki Go Outdoor WiFi Access Point - GR60 Datasheet

Meraki Go Outdoor WiFi Access Point



GR60: Dual-band, 802.11ac Wave 2 2x2:2 MU MIMO

Radios

- 2.4 GHz 802.11b/g/n client access radio
- 5 GHz 802.11a/n/ac client access radio
- Supported frequency bands (country-specific restrictions apply):
 - 2.412-2.484 GHz
 - 5.150-5.250 GHz (UNII-1)
 - 5.250-5.350 GHz (UNII-2)
 - 5.470-5.600, 5.660-5.725 GHz (UNII-2e)
 - 5.725 -5.825 GHz (UNII-3)

802.11ac and 802.11n Capabilities

- 2 x 2 multiple input, multiple output (MIMO) with two spatial streams
- SU-MIMO and MU-MIMO support
- Maximal ratio combining (MRC) & Beamforming
- 20 and 40 MHz channels (802.11n), 20, 40, and 80 MHz channels (802.11ac)
- Up to 256 QAM on both 2.4 GHz and 5 GHz bands
- Packet aggregation

Antenna

- Integrated omni-directional antennas (5.6 dBi gain at 2.4 GHz, 5.3

dBi gain at 5 GHz)

Interfaces

- 1x 10/100/1000 BASE-T Ethernet (RJ45)
- 1x DC power connector (5.5 mm x 2.5 mm, center positive)

Power

- Power over Ethernet: 37 - 57 V (802.3af compatible)
- Alternative 12 V DC input
- Power consumption: 11W max (802.3af)
- Power over Ethernet injector sold separately

Environment

- Operating temperature: -4 °F to 131 °F (-20 °C to 55 °C)
- Humidity: 5 to 95% non-condensing

Physical Dimensions

- 9.56" x 4.48" x 1.18" (243 mm x 114 mm x 30 mm), not including mount plate

Mobility

- PMK and OKC for fast Layer 2 roaming

LED Indicators

- 2 Ethernet status
- 1 power/booting/firmware upgrade status

Compliance

- RoHS
- EN 60601-1-2 EMC requirements for the Medical Directive 93/42/EEC

In the Box

- GR60-HW: Meraki Go Outdoor Access Point
- Wall mount and screw kit
- Quick start guide
- PSU and ethernet cable

Warranty

- 1 year hardware warranty



LGCE
Newtonstraat 8
3281 NM Numansdorp
+31 (0)186 659 510
www.lgce.net